



Glowline

spec sheet

Key features

Tailored: Fully tailorable in curved/straight and angular sections with even light diffusion throughout.

LED: Wide range of light outputs, colour temperatures and colours.

Control: Switched, 0-10V, DALI, DMX and SPI (pixel) dimming protocols.

Material: Acrylic diffuser with anodised and powder coated chassis.

Aesthetic: Flush mounted or proud diffuser with seamless joints and no visible mechanical fixing.

Longevity: 50,000+ LED lifetime expectancy.

Sustainability: Maintainable LED modules.

Application: Interior and exterior in wall, ceiling and suspended applications.


Glowline by The Light Lab



GL12
GL16
GL20
GL25
GL50

the light lab
bright ideas

Product Details GL12



Specification

Output	SO
Power Consumption	9.6W/m
Voltage	24VDC
IP Rating	IP40 or IP65
LED Colour ¹	2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K)
Dimensions:	
Width	12.7mm
Length	115mm to 2965mm in 50mm increments
Depth ²	19.7mm
Mount Type ³	Keyhole (KH), Magnet (MG) & Plaster-in (PL)
Finish	Flush (F) or Proud (P)
Control	0-10V/1-10V/DMX/DALI/SPI

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Other mount types available on request.
- 4 For curved and shaped configurations, please contact the office to discuss your requirements.

Order code

GL12-Output-IP Rating-LED Colour-Mount Type-Finish-Length-Dimming


Example code: GL12-SO-IP40-3.0K-SM-F-2065-DALI

Description: Glowline 12, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with flush diffuser. Length=2065mm DALI dimmable.



Chasis
IP44


IP65




Mount Type

Keyhole (KH)

Magnet (MG)




Plaster-in (PL)



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details GL16



Specification

Output	SO	HO	SHO
Power Consumption	9.6W/m	14.4W/m	18W/m
Voltage	24VDC	24VDC	24VDC
IP Rating	IP40 or IP65	IP40 or IP65	IP40 or IP65
LED Colour ¹	2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K)		
Dimensions:	16mm		
Width	115mm to 2965mm in 50mm increments		
Length	22.9mm		
Depth ²			
Mount Type ³	Keyhole (KH), Magnet (MG) & Plaster-in (PL)		
Finish	Flush (F) or Proud (P)		
Control	0-10V/1-10V/DMX/DALI/SPI		

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables
- 3 Other mount types available on request.
- 4 For curved and shaped configurations, please contact the office to discuss your requirements.

Order code


GL16-Output-IP Rating-LED Colour - Mount Type-Finish-Length-Dimming

Example code: GL16-SO-IP40-3.0K-SM-F-2065-DALI


Description: Glowline 16, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with flush diffuser.
Length=2065mm DALI dimmable.



Chasis
IP44





IP65




Mount Type

Keyhole (KH)

Magnet (MG)




Plaster-in (PL)



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details GL20



Specification

Output	SO	HO	SHO
Power Consumption	9.6W/m	14.4W/m	18W/m
Voltage	24VDC	24VDC	24VDC
IP Rating	IP40 or IP65	IP40 or IP65	IP40 or IP65
LED Colour ¹	2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K)		
Dimensions:	20mm		
Width	115mm to 2965mm in 50mm increments		
Length	27mm		
Depth ²			
Mount Type ³	Keyhole (KH), Magnet (MG) & Plaster-in (PL)		
Finish	Flush (F) or Proud (P)		
Control	0-10V/1-10V/DMX/DALI/SPI		

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Other mount types available on request.
- 4 For curved and shaped configurations, please contact the office to discuss your requirements.

Order code

GL20-Output-IP Rating-LED Colour - Mount Type-Finish-Length-Dimming

Example code: GL20-SO-IP40-3.0K-SM-F-2065-DALI


Description: Glowline 20, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with flush diffuser.
Length=2065mm DALI dimmable.



Chasis

IP44


IP65




Mount Type

Keyhole (KH)

Magnet (MG)



Plaster-in (PL)



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details GL25



Specification

Output	SO	HO	SHO
Power Consumption	9.6W/m	14.4W/m	18W/m
Voltage	24VDC	24VDC	24VDC
IP Rating	IP40 or IP65	IP40 or IP65	IP40 or IP65
LED Colour ¹	2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K)		
Dimensions:	25mm		
Width	115mm to 2965mm in 50mm increments		
Length	32mm		
Depth ²			
Mount Type ³	Keyhole (KH), Magnet (MG) & Plaster-in (PL)		
Finish	Flush (F) or Proud (P)		
Control	0-10V/1-10V/DMX/DALI/SPI		

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Other mount types available on request.
- 4 For curved and shaped configurations, please contact the office to discuss your requirements.

Order code

GL25-Output-IP Rating-LED Colour-Mount Type-Finish-Length-Dimming

Example code: GL25-SO-IP40-3.0K-SM-F-2065-DALI


Description: Glowline 25, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with flush diffuser.
Length=2065mm DALI dimmable.



Chasis

IP44


IP65




Mount Type

Keyhole (KH)

Magnet (MG)



Plaster-in (PL)



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details GL50



Specification

Output	SO	HO	SHO
Power Consumption	9.6W/m	14.4W/m	18W/m
Voltage	24VDC	24VDC	24VDC
IP Rating	IP40 or IP65	IP40 or IP65	IP40 or IP65
LED Colour ¹	2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K)		
Dimensions:	50mm		
Width	115mm to 2965mm in 50mm increments		
Length	55.7mm		
Depth ²			
Mount Type ³	Keyhole (KH), Magnet (MG) & Plaster-in (PL)		
Finish	Flush (F) or Proud (P)		
Control	0-10V/1-10V/DMX/DALI/SPI		

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Other mount types available on request.
- 4 For curved and shaped configurations, please contact the office to discuss your requirements.

Order code

GL50-Output-IP Rating-LED Colour-Mount Type-Finish-Length-Dimming

Example code: GL50-SO-IP40-3.0K-SM-F-2065-DALI



Description: Glowline 50, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with flush diffuser.
Length=2065mm DALI dimmable.



Chasis

IP44



IP65




Mount Type

Keyhole (KH)

Magnet (MG)



Plaster-in (PL)



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas


Project Images



Broadgate Circle



The Engine Room



Bobby Moore Pedestrian Underpass, Wembley



Ashford International




Liberty Specialist Markets



Commercial Office, London



Lake View, Manchester



Admiral, Newport

Glowline by The Light Lab

the light lab
bright ideas