



Glowpanel

spec sheet

Key features

Tailored: Fully tailorable size providing even surface illumination with minimal depth.

LED: Wide range of light outputs, colour temperatures and colours.

Control: Switched, 0-10/1-10v, DALI, DMX and SPI dimming protocols.

Material: Rigid diffusion material chosen to suit application.

Aesthetic: Even illumination and discreet fixing details with trimless options available.

Longevity: 50,000+ LED lifetime expectancy.

Sustainability: Maintainable LED modules.

Application: Interior and exterior wall, ceiling and floor options.


Glowpanel by The Light Lab



Glowpanel
Glowpanel Trimless
Glowpanel LT
Glowpanel Trimless LT
Glowtile

the light lab
bright ideas

Product Details Glowpanel



Specification

| | | |
|-------------------------|--|----------------------------|
| Output | SO | HO |
| Power Consumption | average 56W/m ² | average 72W/m ² |
| Voltage | 24VDC | 24VDC |
| IP Rating | IP40 or IP65 | IP40 or IP65 |
| LED Colour ¹ | 2.0K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K) | |
| Dimensions: | Width | 1500mm (max) |
| | Length | 3000mm (max) |
| | Depth ² | 20mm |
| Mount Type ³ | Surface (SM), Recessed Wall (RE), Wall (WA) or Ceiling (CE) | |
| Finish | Brushed S/Steel or RAL Finish | |
| Control | 0-10V/1-10V/DMX/DALI/SPI | |

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Special mechanical consideration is required for ceiling applications.

Order code

Glowpanel - Output-IP Rating-LED Colour-Mount Type-Frame Finish-
Length x Width(mm)- Dimming

Example code: Glowpanel-SO-IP40-3.0K-SM-BR-1200x300-DALI


Description: Glowpanel, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with brushed stainless steel frame. Overall dimensions = 1200x300mm mm. DALI dimmable.



X Section


IP40

IP65




Mount Type

Wall (WA)



Ceiling (CE)



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details Glowpanel Trimless



Specification

| Output | SO | HO |
|-------------------------|--|---------------------|
| Power Consumption | average 56W/m ² | 210W/m ² |
| Voltage | 24VDC | 24VDC |
| IP Rating | IP40 or IP65 | IP40 or IP65 |
| LED Colour ¹ | 2.0K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K) | |
| Dimensions: | Width 1500mm (max) Length 3000mm (max) Depth ² 35mm (SO) or 50mm (HO) | |
| Mount Type ³ | Surface (SM), Recessed Wall (RE), Wall (WA) or Ceiling (CE) | |
| Finish | White (WH) or Custom RAL (RAL) | |
| Control | 0-10V/1-10V/DMX/DALI/SPI | |

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Special mechanical consideration is required for ceiling applications.

Order code

Glowpanel Trimless- Output-IP Rating-LED Colour-Mount Type-Frame Finish-
Length x Width(mm)- Dimming

Example code: Glowpanel Trimless-SO-IP40-3.0K-SM-BR-1200x300-DALI

Description: Glowpanel Trimless, standard output, IP40, 24VDC constant voltage
LED with 3000K colour temperature. Surface mounted with powder coated chassis.
Overall dimensions = 1200x300mm mm. DALI dimmable.



X Section


SO - IP40




HO - IP40




SO-IP65




HO-IP65



Wall Fixing



Ceiling Fixing



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details Glowpanel LT



Specification

| | | |
|-------------------------|--|--------------------|
| Output | SO | HO |
| Power Consumption | 40W/m ² | 80W/m ² |
| Voltage | 24VDC | 24VDC |
| IP Rating | IP40 | IP40 |
| LED Colour ¹ | 2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K) | |
| Dimensions: | Width | 1200mm (max) |
| | Length | 3000mm (max) |
| | Depth ² | 85mm |
| Mount Type ³ | Ceiling (CE) | |
| Finish | Black (BK) or Custom RAL (RAL) | |
| Control | 0-10V/1-10V/DMX/DALI/SPI | |

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Special mechanical consideration is required for ceiling applications.

Order code

Glowpanel LT- Output-IP Rating-LED Colour-Mount Type-Frame Finish- Length x Width(mm)- Dimming


Example code: Glowpanel LT-SO-IP40-3.0K-CE-BR-1200x300-DALI

Description: Glowpanel LT, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Ceiling mounted with powder coated frame. Overall dimensions = 1200x300mm mm. DALI dimmable.




X Section

IP40




Mount Type

Ceiling (CE)



Photometric Data




Photometric data available late Summer 2022.



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabtd
www.thelightlab.com

the light lab
bright ideas

Product Details Glowpanel Trimless LT



Specification

| | | |
|-------------------------|--|--------------------|
| Output | SO | HO |
| Power Consumption | 40W/m ² | 80W/m ² |
| Voltage | 24VDC | 24VDC |
| IP Rating | IP40 | IP40 |
| LED Colour ¹ | 2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K) | |
| Dimensions: | Width | 1200mm (max) |
| | Length | 3000mm (max) |
| | Depth ² | 60mm |
| Mount Type ³ | Surface (SM), Recessed Wall (RE), Wall (WA) or Ceiling (CE) | |
| Finish | 5 sided acrylic diffuser | |
| Control | 0-10V/1-10V/DMX/DALI/SPI | |

Notes

- 1 Other colours available on request.
- 2 Depth excludes grommet, glands & cables.
- 3 Special mechanical consideration is required for ceiling applications.

Order code


Glowpanel Trimless LT- Output-IP Rating-LED Colour-Mount Type-Frame Finish- Length x Width(mm)- Dimming

Example code: Glowpanel Trimless LT-SO-IP40-3.0K-SM-BR-1200x300-DALI


Description: Glowpanel Trimless LT, standard output, IP40, 24VDC constant voltage LED with 3000K colour temperature. Surface mounted with 5 sided acrylic diffuser. Overall dimensions = 1200x300mm mm. DALI dimmable.

X Section

IP40




IP65




Mount Type

Ceiling (CE)



Photometric Data




Photometric data available late Summer 2022.



The Light Lab
22 Holywell Row
London EC2A 4JB
+44 (0) 207 278 2678
@thelightlabltd
www.thelightlab.com

the light lab
bright ideas

Product Details Glowtile



Specification

| | | |
|-------------------------|---|---------------------|
| Output | SO | HO |
| Power Consumption | average 56W/m ² | 210W/m ² |
| Voltage | 24VDC | 24VDC |
| IP Rating | IP67 | IP67 |
| LED Colour ¹ | 2.7K/3.0K/4.0K/5.0K, RGBW or WWCW (White Mix 2.7K - 6.5K) | |
| Dimensions: | Width | 1000mm (max) |
| | Length | 1500mm (max) |
| | Depth | 76.2mm |
| Mount Type | Inground (IN) | |
| Finish | White (WH) or Custom RAL (RAL) | |
| Control | 0-10V/1-10V/DMX/DALI/SPI | |

Notes

1 Other colours available on request.

Order code


Glowtile- Output-IP Rating-LED Colour-Mount Type-Frame Finish- Length x Width(mm)-Dimming

Example code: Glowtile-SO-IP67-3.0K-IN-WH-1200x300-DALI

Description: Glowtile, standard output, IP67, 24VDC constant voltage LED with 3000K colour temperature. Inground with white powdercoat frame. Overall dimensions = 1200x300mm mm. DALI dimmable.



X Section



The Light Lab
 22 Holywell Row
 London EC2A 4JB
 +44 (0) 207 278 2678
 @thelightlabtd
 www.thelightlab.com

the light lab
 bright ideas

Project Images



Sadler's Wells



Breakspear Park



85 Finsbury Square



Great Western Arcade



12 Arthur St



Waterloo Station



Ropemaker Place