

Main Features


- O Even surface illumination with minimal depth
- O Polished stainless steel frame system for high end finish
- O Trimless design available
- O 50 000+ hr lifetime expectancy
- O IP44 or IP65 interior/exterior application
- O Hidden fixing to suit application

LED Panel by The Light Lab



LED Panel
LED Trimless Panel
LED Trimless Lightbox
LED Trimless Ceiling Panel
LED Light Tile
Glowsheet
LED Matrix

Product Details LED Panel



Specification

Dimensions	Max width - 1500mm Max length - 3000mm Min depth - 20mm
Colour	2.7K/3.0K/3.5K/4.0K/5.0K others on application
Input Voltage	24 Vdc
Power Consumption	Approx - 40W sq/M
IP Rating	IP44 or IP65
Lumen Output	c. 3200 lm/sq metre
Frame Finish	Stainless Steel or RAL to finish
Fixing	Wall or Ceiling

Order code

LED PANEL-WIDTH-LENGTH-DEPTH-COLOUR-IP-FINISH-FIXING e.g. LED PANEL-XXmm-XXmm-XXmm-2.7K-IP44-SS-MAGNET

WIDTH -	LENGTH	-	DEPTH	-	COLOUR	-	IP -	FINISH	-	FIXING
XXmm	XXmm		XXmm		2.7K		P44	SS		Wall
					3.0K	H	P65	RAL		Ceiling
					3.5K					
					4.0K					
					5.0K					

Drivers


non-dimmable power supplies:


1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application LED Panel by The Light Lab

\uparrow

Fixing Methods





Project Images







Product Details LED Trimless Panel



Specification

	so	но
Dimensions	Max width - 1500mm Max length - 3000mm Standard depth - 50mm	Max width - 1500mm Max length - 3000mm Standard depth - 50mm
Colour	2.7K/3.0K/3.2K/ 3.8K/4.0K/5K	2.7K/3.0K/3.2K/ 3.8K/4.0K/5K
Input Voltage	24Vdc	24Vdc
Power Consumption	max 56W/sq m	155W/sq m
IP Rating	IP44 or IP65	IP 44 or IP 65
Lumen Output	max 3200 lm/ sq m	9525 lm/ sq m
Frame Finish	White	White
Fixing	Wall or Ceiling	Wall or Ceiling

Order code

LED TRIMLESS PANEL-WIDTH-LENGTH-DEPTH-COLOUR-IP-FINISH-FIXING e.g. LED TRIMLESS PANEL-XXmm-XXmm-XXmm-2.7K-IP44-SS-MAGNET

WIDTH -	LENGTH -	DEPTH	-	COLOUR	-	IP -	FINISH	-	FIXING
XXmm	XXmm	XXmm		2.7K		IP44	White		Wall
				3.0K		IP65			Ceiling
				3.5K					
				4.0K					
				5 OK					

Drivers


non-dimmable power supplies:

1-10V /DALI/DMX dimmable power supplies to be ordered seperately


Please call our sales team who will make sure specification suits application LED Trimless Panel by The Light Lab

$\dot{\uparrow}$

Fixing Methods



CEILING FIXING




Project Images





Product Details LED Trimless Lightbox



Specification

	so	НО
Dimensions	Max 1.0m x 3.0m 80mm Depth	Max 1.0m x 3.0m 50mm Depth
Colour	2.7K/3.0K/3.2K/ 3.8K/4.0K/5K	2.7K/3.0K/3.2K/ 3.8K/4.0K/5K
Input Voltage	24VDC	24VDC
Power Consumption	110W/sqm	150W/sqm
IP Rating	IP44	IP44
Lumen Out- put	84 lm/W	84 lm/W
Frame Finish	Acrylic	Acrylic
Fixing	Rod or Fastmount	Rod or Fastmount

Order code

LED TRIMLESS LIGHTBOX-WIDTH-LENGTH-DEPTH-COLOUR-IP-FINISH-FIXING e.g. LED TRIMLESS LIGHTBOX-XXmm-XXmm-XXmm-2.7K-IP44-SS-MAGNET

FIXING WIDTH - LENGTH - DEPTH - COLOUR - IP - FINISH - XXmm XXmm 2.7K IP44 Acrylic 3.0K 3.2K 3.5K 3.8K 4.0K/5.0K


Drivers

non-dimmable power supplies:


1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application LED TRIMLESS LIGHTBOX by The Light Lab

X-SECTION



FIXINGS



Project images







Product Details LED Trimless Ceiling Panel



Specification

	SO	НО
Dimensions	Max 3.0M x 1.2M x 80mm depth	Max 3.0m x 12.M x 50mm depth
Colour	2.7K/3.0K/3.2K/ 3.8K/4.0K/5K	2.7K/3.0K/3.2K/ 3.8K/4.0K/5K
Input Voltage	24VDC	24VDC
Power Consumption	110W/sqm	150W/sqm
IP Rating	IP44	IP44
Lumen Output	95 lm/W	95 lm/W
Frame Finish	RAL t.b.c.	RAL t.b.c.
Fixing	PIN fixings or fastmount	PIN fixings or fastmount

Order code

LED TRIMLESS CEILING PANEL-WIDTH-LENGTH-DEPTH-COLOUR-IP-FINISH-FIXING e.g. LED TRIMLESS CEILING PANEL-XXmm-XXmm-XXmm-2.7K-IP44-WHITE-FRAME

WIDTH -	LENGTH	-	DEPTH	-	COLOUR	- IP	-	FINISH	-	FIXING
XXmm	XXmm		XXmm		2.7K	IP44	-	White		PIN fixings
					3.0K					Frame
					3.2K					
					3.5K					
					4.0K					
					5.0K					


Drivers

non-dimmable power supplies:


1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application LED Trimless Ceiling Panel by The Light Lab

X-SECTION



FIXING OPTION



Project images










Product Details LED Light Tile



Specification

Dimensions	Max width - 1000mm Max length - 1500mm Min depth - 80mm
Colour	2.7K/3.0K//4.0K/5.0K or RGB
Input Voltage	24 Vdc
Power Consumption	Approx - 40W sq/M
IP Rating	IP67
Finish	316 Stainless Steel
Loadings	Drive Over or Walk Over Loadings to suit
Fixings	Adjustable feet

Order code

LED LIGHT TILE-WIDTH-LENGTH-DEPTH-COLOUR-IP-LOADINGS e.g. LED TRIMLESS PANEL-XXmm-XXmm-2.7K-IP67-SS-DO

 WIDTH LENGTH DEPTH COLOUR IP FINISH LOADINGS

 XXmm
 XXmm
 2.7K
 IP67
 SS
 DO

 3.0K
 WO

 4.0K
 5.0K

RGB

Drivers


non-dimmable power supplies:

1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application LED Panel by The Light Lab



X-Section



Project Examples










Product Details Glowsheet



Specification

Dimensions	Max width - 2000mm Max length - 3000mm
Material Thickness	5mm/8mm/10mm or 12mm
LED Colours	2.7K/3.0K/3.5K/4.0K/5.0K/ or Single Colours to suit RGB/RGBCW/RGBWW or White Mix 2.7K/6.5K

Input Voltage 24Vdc

IP Rating IP20 or IP65

Frame Finish Aluminium

Order code

GLOWSHEET-WIDTH-LENGTH-THICKNESS-COLOUR-IP-FINISH e.g. GLOWSHEET-XXmm-XXmm-XXmm-2.7K-IP20-ALI

8mm 3.0K IP65 10mm 3.5K 4.0K 5.0K RGB RGBCW RGBWW WM 3.0K	
WM 3.0K WM 5.0K	

Drivers


non-dimmable power supplies:

1-10V /DALI/DMX dimmable power supplies to be ordered seperately


Please call our sales team who will make sure specification suits application LED Panel by The Light Lab

Typica

Typical X-Section




Project Examples







Product Details: LED Matrix



Specification

Specification	11		
	SO	НО	W/Mix
Dimension	275mm x 275mm	275mm x 275mm	275mm x 275mm
Colour	2.7K/3.0K/3.2K/ 3.5K/4.0K/5.0K	2.7K/3.0K/3.2K/ 3.5K/4.0K/5.0K	2.7K/6.9K
Input Voltage	24Vdc	24Vdc	24Vdc
Power Consumption	8.4W	11.5W	17.2W
LED Pitch	39mm	22mm	39mm
Luminaire Efficiency	120 lm/W	120 lm/W	110 lm/W
Operating temp	-15 ° + to 40 °	-15 ° + to 40 °	-15 ° + to 40 °

Order code

LinLED MATRIX-DIM-output-COLOUR-PITCH e.g. LED MATRIX-XX-SO-3.0K-39mm

DIM -	OUTPUT	-	COLOUR	-	PITCH
XXmm	SO		2.7K		39mm
	НО		3.0K		22mm
	W/MIX		3.2K		
			3.5K		
			4.0K		
			5.0K		
			COV		

Drivers

non-dimmable power supplies:


1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application Linear LED Lighting by The Light Lab





X-Sections

	275mm		
· • • · ·	• • · •	2	
. © . • . II F	nel II.	275mm	
		io	
		-	



137.5mm





Project Example






Project Images



Sadler's Wells Theatre







Waterloo Station



Wallbrook



48 Leicester Square



One Canada Square