LED Panel


spec sheet

Main Features

- O Even surface illumination with minimal depth
- O Polished stainless steel frame system for high end finish
- O Trimless design available
- O 50 000+ hr lifetime expectancy
- O IP44 or IP65 interior/exterior application
- O Hidden fixing to suit application




LED Panel LED Trimless Panel LED Trimless Lightbox LED Trimless Ceiling Panel LED Light Tile Glowsheet LED Matrix is dance



non-dimmable power supplies: 1-10V /DALI/DMX dimmable power supplies to be ordered seperately


Please call our sales team who will make sure specification suits application

22 Holywell Row London EC2A 4JB United Kingdom +44 (0) 207 278 2678 @thelightlabltd www.thelightlab.com




@thelightlabltd www.thelightlab.com

Please call our sales team who will make sure specification suits application



@thelightlabltd www.thelightlab.com

Please call our sales team who will make sure specification suits application




@thelightlabltd

www.thelightlab.com

Please call our sales team who will make sure specification suits application LED Trimless Ceiling Panel by The Light Lab

Product Details LED Light Tile



Specification

Dimensions	Max width - 1000mm Max length - 1500mm Min depth - 80mm
Colour	2.7K/3.0K//4.0K/5.0K or RGB
Input Voltage	24 Vdc
Power Consumption	Approx - 40W sq/M
IP Rating	IP67
Finish	316 Stainless Steel
Loadings	Drive Over or Walk Over Loadings to suit
Fixings	Adjustable feet

Order code

LED LIGHT TILE-WIDTH-LENGTH-DEPTH-COLOUR-IP-LOADINGS e.g. LED TRIMLESS PANEL-XXmm-XXmm-2.7K-IP67-SS-DO


WIDTH - LENGTH - DEPTH - COLOUR - IP - FINISH - LOADINGS XXmm XXmm XXmm 2.7K IP67 SS DO 3.0K WO 4.0K 5.0K RGB

Drivers

non-dimmable power supplies:

1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application



Project Examples








the light lab

The Light Lab 22 Holywell Row

22 Holywell Row London EC2A 4JB United Kingdom +44 (0) 207 278 2678 @thelightlabltd www.thelightlab.com



Product Details: LED Matrix

Specification

	SO	но	W/Mix
Dimension	275mm x 275mm	275mm x 275mm	275mm x 275mm
Colour	2.7K/3.0K/3.2K/ 3.5K/4.0K/5.0K	2.7K/3.0K/3.2K/ 3.5K/4.0K/5.0K	2.7K/6.9K
Input Voltage	24Vdc	24Vdc	24Vdc
Power Consumption	8.4W	11.5W	17.2W
LED Pitch	39mm	22mm	39mm
Luminaire Efficiency	120 lm/W	120 lm/W	110 lm/W
Operating temp	-15 ° + to 40 °	-15 ° + to 40 °	-15 ° + to 40 °

Order code


LinLED MATRIX-DIM-output-COLOUR-PITCH e.g. LED MATRIX-XX-SO-3.0K-39mm

DIM -	OUTPUT	- COLOUR	- PITCH
XXmm	SO	2.7K	39mm
	НО	3.0K	22mm
	W/MIX	3.2K	
		3.5K	
		4.0K	
		5.0K	
		6.9K	

Drivers

non-dimmable power supplies: 1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application



i

the ^{bright}	light l ^{ideas}	ab	

C

The Light Lab 22 Holywell Row London EC2A 4JB United Kingdom +44 (0) 207 278 2678 @thelightlabltd www.thelightlab.com

Project Images



Sadler's Wells Theatre



Ropemaker Place



Breakspear Park



Wallbrook



48 Leicester Square





Waterloo Station

One Canada Square