

Glowscreen

spec sheet

Main Features

- Illuminated fabric tension system across a lightweight frame
- Versatile digital fabric printing process to ensure maximum luminosity (PVC free)
- Available in a range of light outputs/colour temperatures & full colour changing RGB
- Simple frame assembly - lightweight and portable
- Easily exchangeable graphics
- Options available for wall/ceiling mounted or free-standing
- Slimline frame depth of 65mm / 120mm
- Can be manufactured to any bespoke size from A4 to large scale structural features - up to 5m x 50m
- Internal or external application

Glowscreen by The Light Lab



Glowscreen

Product Details Glowscreen



Specification

	SO	HO
Size	Up to 5m x 50m	Up to 5m x 50m
Height	125mm	65mm
Depth	120mm	65mm
LED Option	3000K/4000K/ 5000K/RGB/RGBW/ RGBWW	3000K/4000K/ 5000K/RGB/RGBW/ RGBWW
Input Voltage	24VDC	24VDC
Efficacy	140W/m ²	176W/m ²
IP Rating	IP44	IP44
Luminaire Lumens	9500 lms/m ²	12100 lms/m ²
CRI	780	780
LED Drivers	Dali Dimmable/110/DMX	Dali Dimmable/110/DMX

Order code

GLOWSCREEN-SIZE-HEIGHT-DEPTH-LED-IP
e.g. GLOWSCREEN-XXmm-XXmm-XXmm-3.0K-IP44

SIZE - HEIGHT - DEPTH - LED - IP
XXmm XXmm 65mm 3.0K IP44

Drivers

non-dimmable power supplies:

1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application


Glowscreen by The Light Lab



X Section



Profile 120
Standard Output



Profile 65
High output

Project images



The Light Lab
22 Holywell Row
London EC2A 4JB
United Kingdom
+44 (0) 207 278 2678
@thelightlabtd
www.thelightlab.com