



# LED Panel

spec sheet

## Main Features


- Even surface illumination with minimal depth
- Polished stainless steel frame system for high end finish
- Trimless design available
- 50 000+ hr lifetime expectancy
- IP44 or IP65 interior/exterior application
- Hidden fixing to suit application

LED Panel by The Light Lab



LED Panel  
LED Trimless Panel  
LED Light Tile  
Glowsheet

# Product Details LED Panel



## Specification

Dimensions	Max width - 1500mm Max length - 3000mm Min depth - 20mm
Colour	2.7K/3.0K/3.5K/4.0K/5.0K others on application
Input Voltage	24 Vdc
Power Consumption	Approx - 40W sq/M
IP Rating	IP44 or IP65
Lumen Output	c. 3200 lm/sq metre
Frame Finish	Stainless Steel or RAL to finish
Fixing	Wall or Ceiling

**Order code**  
LED PANEL-WIDTH-LENGTH-DEPTH-COLOUR-IP-FINISH-FIXING  
e.g. LED PANEL-XXmm-XXmm-XXmm-2.7K-IP44-SS-MAGNET



WIDTH	LENGTH	DEPTH	COLOUR	IP	FINISH	FIXING
XXmm	XXmm	XXmm	2.7K	IP44	SS	Wall
			3.0K	IP65	RAL	Ceiling
			3.5K			
			4.0K			
			5.0K			

**Drivers**  
non-dimmable power supplies:  
1-10V /DALI/DMX dimmable power supplies to be ordered seperately


Please call our sales team who will make sure specification suits application  
LED Panel by The Light Lab



## Fixing Methods



## Photometric Info



The Light Lab  
22 Holywell Row  
London EC2A 4JB  
United Kingdom  
+44 (0) 207 278 2678  
@thelightlabtd  
www.thelightlab.com

# Product Details LED Trimless Panel



## Specification

	SO	HO
Dimensions	Max width - 1500mm Max length - 3000mm Standard depth - 50mm	Max width - 1500mm Max length - 3000mm Standard depth - 50mm
Colour	2.7K/3.0K/3.5/4.0K/5.0K others on application	2.7K/3.0K/3.5/4.0K/5.0K others on application
Input Voltage	24Vdc	24Vdc
Power Consumption	max 56W/sq m	155W/sq m
IP Rating	IP44 or IP65	IP 44 or IP 65
Lumen Output	max 3200 lm/ sq m	9525 lm/ sq m
Frame Finish	White	White
Fixing	Wall or Ceiling	Wall or Ceiling

### Order code

LED TRIMLESS PANEL-WIDTH-LENGTH-DEPTH-COLOUR-IP-FINISH-FIXING  
e.g. LED TRIMLESS PANEL-XXmm-XXmm-XXmm-2.7K-IP44-SS-MAGNET

WIDTH - LENGTH - DEPTH - COLOUR - IP - FINISH - FIXING  
XXmm XXmm XXmm 2.7K IP44 White Wall  
3.0K IP65 Ceiling  
3.5K  
4.0K  
5.0K

### Drivers

non-dimmable power supplies:



1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application


LED Panel by The Light Lab



## Fixing Methods




## Photometric Info



The Light Lab  
22 Holywell Row  
London EC2A 4JB  
United Kingdom  
+44 (0) 207 278 2678  
@thelightlabld  
www.thelightlab.com



# Product Details LED Light Tile



## Specification

Dimensions	Max width - 1000mm Max length - 1500mm Min depth - 80mm
Colour	2.7K/3.0K//4.0K/5.0K or RGB
Input Voltage	24 Vdc
Power Consumption	Approx - 40W sq/M
IP Rating	IP67
Finish	316 Stainless Steel
Loadings	Drive Over or Walk Over Loadings to suit
Fixings	Adjustable feet

### Order code

LED LIGHT TILE-WIDTH-LENGTH-DEPTH-COLOUR-IP-LOADINGS  
e.g. LED TRIMLESS PANEL-XXmm-XXmm-2.7K-IP67-SS-DO

WIDTH	LENGTH	DEPTH	COLOUR	IP	FINISH	LOADINGS
XXmm	XXmm	XXmm	2.7K	IP67	SS	DO
			3.0K			WO
			4.0K			
			5.0K			
			RGB			


### Drivers

non-dimmable power supplies:



1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application

LED Panel by The Light Lab



## Project Examples




GETTING MORE PROJECT IMAGES



The Light Lab  
22 Holywell Row  
London EC2A 4JB  
United Kingdom  
+44 (0) 207 278 2678  
@thelightlabld  
www.thelightlab.com

# Product Details GLED Panel



## Specification

Dimensions	Max width - 2000mm Max length - 3000mm
Material Thickness	5mm/8mm/10mm or 12mm
LED Colours	2.7K/3.0K/3.5K/4.0K/5.0K/ or Single Colours to suit RGB/RGBCW/RGBWW or White Mix 3.0K/5.0K
Input Voltage	24Vdc
IP Rating	IP20 or IP65
Frame Finish	Aluminium

### Order code

GLOWSHEET-WIDTH-LENGTH-THICKNESS-COLOUR-IP-FINISH  
e.g. GLOWSHEET-XXmm-XXmm-XXmm-2.7K-IP20-ALI

WIDTH	LENGTH	THICKNESS	COLOUR	IP	FINISH
XXmm	XXmm	5mm	2.7K	IP20	ALI
		8mm	3.0K	IP65	
		10mm	3.5K		
			4.0K		
			5.0K		
			RGB		
			RGBCW		
			RGBWW		
			WM 3.0K		
			WM 5.0K		

### Drivers

non-dimmable power supplies:


1-10V /DALI/DMX dimmable power supplies to be ordered seperately

Please call our sales team who will make sure specification suits application

LED Panel by The Light Lab



## Typical X-Section



## Project Examples



The Light Lab  
22 Holywell Row  
London EC2A 4JB  
United Kingdom  
+44 (0) 207 278 2678  
@thelightlabld  
www.thelightlab.com





Sadler's Wells Theatre



The Wallbrook



Ropemaker Place



Movida



33 Kingsway



Victoria Marketing Suite



One Canada Square